

PRO-TECT ULTRA SHINE PLUS



Start A New Tradition With PTU Shine Plus

PTU Shine Plus is a tough two-part microfiber applied urethane gloss coating for resilient, concrete, and terrazzo flooring.

- The ideal gloss coating for concrete, terrazzo and resilient flooring
- High performance microfiber applied coating
- Fast cure time, allows space to be returned to service quicker
- Coverage: 1,800 sf/gal



Pre-Application:

Prior to application, the space should be conditioned and between 60-80 degrees Fahrenheit. Surface should be properly prepared and cleaned.

1. All acrylic finishes should be removed
2. Any existing urethane coating showing flaking, or yellowing should be removed
3. Surface should be agitated using a 3M Scotch-Brite Surface Preparation Pad Plus (SPP) pad (or equivalent)
4. Floor must be final cleaned using XL PTU Coating Prep for proper adhesion to occur

Mixing

1. Shake PTU Shine Plus bottle to suspend any settlement
2. Add "PTU Part B" into bottle.
3. Secure lid and shake PTU Shine Plus bottle for approximately 2 minutes.
4. Allow mixture to settle for 5 minutes before use (pot life of mixed material is approximately 8 hours)

Application

1. Pre-charge your 3m Scotchgard Floor protector applicator pad (Blue) or equivalent with mixed PTU Shine Plus
2. Apply PTU Shine Plus in manageable puddles or streams to the floor. For best results, apply material in a linear direction "Box Pattern" (as opposed to figure 8 or swirl) completely covering the area with a thin even coat (approximately 1600 sf per gallon)
3. Allow coating to dry (depending on temperature and humidity approximately 30 minutes)
4. Apply second coat opposite direction as the first.
5. Allow coating to dry
6. If desired, high-speed buffing with a 3m Natural Blend 3500 pad and/or a 3M 3050 Burnishing pad can be done (Dust with clean microfiber pad recoating or prior to re-coating)
7. Allow coating to dry for at least 2 hours prior to re-opening space for foot traffic. (Do not scrub or mop the floor for at least 48 hours after application of coating)
8. Wait 24 hours before moving furniture in.

NOTE: VCT or other flooring types may require a 3rd coat

Maintenance of coating

There is no better way to maintain the appearance of your flooring than to have in place a well-designed maintenance program including proper walk off matting. As with any coating or finish, daily maintenance is recommended to remove debris that may have the potential to abrade the surface.

Daily – Dust mop and spot damp mop as needed

Routine maintenance – Neutral cleaner like XL APC or XL LVT/Wood Floor Cleaner, white pad (or equivalent brush)

Periodic cleaning – Neutral cleaner Like XL APC or XL LVT/Wood Floor Cleaner with red pad (or equivalent brush)

Deep/restorative – Neutral cleaner like XL APC with red or blue pad (or equivalent brush)

Re-coating – when needed, abrad the surface using a 3m SPP pad (or equivalent) and follow the coating steps above.